



VOLVO

Safety Cage Design in the Volvo XC90

Jonas Bernquist
Volvo Car Corporation





VOLVO

Presentation overview

- General
- Body structure
 - Safety cage
 - XC90: New structural solutions
- Materials
 - General
 - XC90: Materials
- Sum-up





VOLVO

General

The first Volvo SUV?



1943




2002





VOLVO

General Key attributes

SIZE [mm]	Length		P28
	Width		4798
	Height		1890
Weight [kg]	Body shell incl frt bumper		1740
	Total hang on		407
	Paint and sealings		113,0
	Body complete incl closures		16,4
	2nd row seat subframe (structural part)		536,4
	Body complete incl 2nd row subframe		17,6
Attributes	Body complete incl 2nd row subframe		554,0
	Static Torsional Stiffness BIG [kNm/deg]		21,4
	1st Dynamic Torsion mode BIG [Hz]		33,6
	1st Dynamic Lateral Bending mode BIG [Hz]		44,1
	1st Dynamic Vertical Bending mode BIG [Hz]		47,4





VOLVO

General Advanced Body Engineering


Complete vehicle Properties



Car Body Properties



Basic Body Technology Parameters






VOLVO

Body structure Safety cage 1

“A rigid framework surrounding the occupants which creates a support for the interior safety equipment and provides a survival space for the vehicle occupants in case of a crash”







VOLVO

Body structure Safety cage 2: SIPS

Side Impact Protection System



- Introduced in 1991
- The structure minimises the intrusion by the:
 - very strong B-pillars
 - rigid rockers
 - transverse floor/roof members
 - SIPS-box
 - framework of the front seats



VOLVO

Body structure New structural solutions

The XC90 BIW challenge

S80



V70




S60



- Increased front crash demands
- Compatibility small cars
- Rollover protection
- Protection 3rd row
- Increased side-impact protection

P2x-platform




Body implications:

New structural and material solutions!




VOLVO

Body structure XC90 dimensions



Kerb weight: 2070kg

Comparison with other cars on the P2x-platform



Width (mm)

S80: 1832

V70: 1804

S60: 1804

Kerb weight (kg)

1631

1670

1574

Length (mm)

S80: 4822

V70: 4710

S60: 4576

Height (mm)

1434

1488 (XC1562)

1428



VOLVO



Body Structure

New structural solutions: Front

New front structure


- To handle higher forces and weight
- Centre floor is carry over P2 platform
- “Three leg support”
- Cross member firewall

Three leg support



S60

XC90



Compatibility

- SUV hitting car
- Different side rail heights
- Engine sub frame (cradle) reinforced and extended forward
- Height aligned with car rail height



VOLVO

Body Structure

New structural solutions: Safety cage - Side

1st attempt



Low hit

Side impact common accident type


SUV hit by SUV

Side impact + higher rollover requirement

Controlled deformation



New demands...



Roof bow collapse

B-pillar collapse


High hit



Too big intrusion

Preferred B-pillar intrusion and deformation mode

Reinforced side- and roof structure



Dual piece sunroof frame clinched together

Strong B-pillar, B roof bow and seat belt bracket



New seat crossmbr



★★★★★ !
EuroNCAP



VOLVO

Body Structure

New structural solutions: Safety cage - Roof

Rollover accidents



Increased req's rollover impact

Heavy vehicle

Strong structure


Packaging

New demands...



Reinforced side- and roof structure

No structural collapse allowed.



Strong B-pillar, B roof bow and A-pillar upper



Dual piece sunroof frame clinched together



EHSS-reinforced A-pillar




Result:
No structural collapse!



VOLVO

Materials

General: Why HSS/EHSS/UHSS?



Annual total weight increase of 10 kg, platform to platform!





VOLVO


Materials

General: High strength steels at VCC

- **HSS**: Rephosphorized & HSLA steels. VCC “standard qualities for high strength material. Slightly better formability with Rephos.

- **HSS/EHSS**: Dual phase steels, used for reinforcements.

- **UHSS**: Boron steel. Used for reinforcements subjected to extreme load cases.



Using HSS/EHSS/UHSS for cost efficient weight reduction !









VOLVO

Materials

XC90: Side-impact & roll-over

-  Boron Steel
-  DP600
-  Rephos ($\sigma_{\text{tensile min}} = 380 \text{ MPa}$)












VOLVO

Materials

XC90 BIW Material distribution




	$Rm_{max} \approx 300$ MPa	} MS	42%
	$Rm_{min} > 340$ MPa (DP, HSLA el Rephos)		
	$Rm_{min} > 380-420$ MPa (DP, HSLA el Rephos)	} HSS	36%
	$Rm_{min} > 600$ MPa (DP600)		
	$Rm_{min} > 1400$ MPa (Boron steel)	} UHSS	6,5%
		} AI	1%




UHSS

HSS



- Body structure 407 kg
- Hang on parts 113 kg
- Polymer tailgate ~11 kg

EHSS



HSS





VOLVO

Sum-up

Ratings



	<u>Europe</u>	<u>USA</u>
Front	★★★★★	★★★★★
Side	★★★★★	★★★★★





VOLVO

Sum-up

- XC90 incorporated several, for Volvo, new structural concepts and material applications
- High degree of HSS-material in the body structure (HSS→EHSS→UHSS)
- Extremely strong upper body structure for good rollover properties





VOLVO

Thank you for your attention!

